



OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI 14 - Plastics Piping System Components and Related Materials

This is the Official Listing recorded on October 5, 2021.

Nupi Industrie Italiane SpA
Via Stefano Ferrario Z.I. Sud-Ovest
21052 Busto Arisizio (VA)
Italy
39 03 313 44211

Facility: Busto Arsizio (VA), Italy

Potable Water - Pipe and Fittings

Table with 4 columns: Product Type, Material Type, Trade Name, Product Standard. Lists various pipe and fitting specifications including sizes, materials, and standards.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



90° Elbow - Long Spigot (Injected Alongated) §	SDR 17	
27NG9017355MMC 14"	27NG9017400MMC 16"	27NG9017450MMC 18"
90° Elbow - Long Spigot (Segmented Fitting) §	SDR 7.3	
27NG9073200MMB 8"	27NG9073200MMB 10"	27NG9073315MMB 12"
27NG9073355MMB 14"		
90° Elbow - Long Spigot (Segmented Fitting) §	SDR 11	
27NG9011315MMB 12"	27NG9011355MMB 14"	27NG9011400MMB 16"
27NG9011450MMB 18"	27NG9011500MMB 20"	
90° Elbow - Long Spigot (Segmented Fitting) §	SDR 17	
27NG9017315MMA 12"	27NG9017315MMB 12"	27NG9017355MMB 14"
27NG9017400MMB 16"	27NG9017450MMB 18"	27NG9017500MMB 20"
27NG9017560MMB 22"	27NG9017630MMB 24"	
Butt Weld - Socket Fusion Tee §	SDR 7.3	
27NT7463MM 2"	27NT7490MM 3"	27NT74110MM 3 1/2"
27NT74125MM 4"	27NT74160MM 6"	
Butt Weld 45° Elbow - Long Spigot §	SDR 7.3	
27NC457463MM 2"	27NC457490MM 3"	27NC4574110MM 3 1/2"
27NC4574125MM 4"	27NC4574160MM 6"	
Butt Weld 45° Elbow - Long Spigot §	SDR 11	
27NC451163MM 2"	27NC451190MM 3"	27NC4511110MM 3 1/2"
27NC4511125MM 4"	27NC4511160MM 6"	27NC4511200MM 8"
27NC4511250MM 10"	27NC4511315MM 12"	
Butt Weld 45° Elbow - Long Spigot §	SDR 17	
27NC451763MM 2"	27NC451790MM 3"	27NC4517110MM 3 1/2"
27NC4517125MM 4"	27NC4517160MM 6"	27NC4517200MM 8"
27NC4517250MM 10"	27NC4517315MM 12"	
Butt Weld 90° Elbow - Long Spigot §	SDR 7.3	
27NG907463MM 2"	27NG907490MM 3"	27NG9074110MM 3 1/2"
27NG9074125MM 4"	27NG9074160MM 6"	
Butt Weld 90° Elbow - Long Spigot §	SDR 11	
27NG901163MM 2"	27NG901190MM 3"	27NG9011110MM 3 1/2"
27NG9011125MM 4"	27NG9011160MM 6"	27NG9011200MM 8"
27NG9011250MM 10"	27NG9011315MM 12"	
Butt Weld 90° Elbow - Long Spigot	SDR 17	
27NG901763MM 2"	27NG901790MM 3"	27NG9017110MM 3 1/2"
27NG9017125MM 4"	27NG9017160MM 6"	27NG9017200MM 8"
27NG9017250MM 10"	27NG9017315MM 12"	
Butt Weld Tee - Long Spigot §	SDR 11	
27NT1163MM 2"	27NT1190MM 3"	27NT11110MM 3 1/2"
27NT11125MM 4"	27NT11160MM 6"	27NT11200MM 8"
27NT11250MM 10"		
Butt Weld Tee - Long Spigot §	SDR 17	
27NT1763MM 2"	27NT1790MM 3"	27NT17110MM 3 1/2"
27NT17125MM 4"	27NT17160MM 6"	27NT17200MM 8"
27NT17250MM 10"		
Compact Cross Over F/F - Socket §		
27NSOFF20 1/2"	27NSOFF25 3/4"	
Compact Cross Over M/F - Socket §		

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



2" x 2 1/2" x 3/4" NPT (27NGSF346375NPT)
2" x 2 1/2" x 1" (27NGSF016375NPT)
3" x 3/4" NPT (27NGSF9034NPT)
3" x 3 1/2" x 4" x 1/2" NPT (27NGSF1290110125NPT)
3" x 3 1/2" x 4" x 3/4" NPT (27NGSF3490110125NPT)
3" x 3 1/2" x 4" x 1" NPT (27NGSF0190110125NPT)
Female Thread 90° Ell NPT & Brass Socket §
27NGOF2012NPT 1/2" x 1/2" 27NGOF2512NPT 3/4" x 1/2"
Female Threaded 90° Elbow for Template ~ §
1/2" x 3/8" NPT (27NGOF2012NPT)
3/4" x 1/2" NPT (27NGOF2512NPT)
Female Threaded Adapter w/NPT Lead Free Brass §
1/2" x 1/2" NPT (27NRFF2012NPT)
1/2" x 3/4" NPT (27NRFF2034NPT)
3/4" x 1/2" NPT (27NRFF2512NPT)
3/4" x 3/4" NPT (27NRFF2534NPT)
1" x 3/4" NPT (27NRFF3234NPT)
1" x 1" NPT (27NRFF321NPT)
1-1/4" x 1" NPT (27NRFF401NPT)
1-1/4" x 1-1/4" NPT (27NRFF40114NPT)
1-1/2" x 1-1/4" NPT (27NRFF50114NPT)
1-1/2" x 1-1/2" NPT (27NRFF50112NPT)
2" x 1-1/2" NPT (27NRFF63112NPT)
2" x 2" NPT (27NRFF632NPT)
2-1/2" x 2" NPT (27NRFF752NPT)
2-1/2" x 2-1/2" NPT (27NRFF75212NPT)
3" x 3" NPT (27NRFF903NPT)
3-1/2" x 4" NPT (27NRFF1104NPT)
4" x 4" NPT (27NRFF1254NPT)
Female Threaded Street 90° Elbows ~ §
1/2" x 1/2" NPT (27NGMFF2012NPT)
Female Threaded Tee w/NPT Lead Free Brass §
1/2" x 1/2" NPT (27NTF2012NPT) 3/4" x 1/2" NPT (27NTF2512NPT)
3/4" x 3/4" NPT (27NTF2534NPT) 1" x 1/2" NPT (27NTF3212NPT)
1" x 3/4" NPT (27NTF3234NPT) 1" x 1" NPT (27NTF321NPT)
Female Threaded Winged 90° ~ §
1/2" x 3/8" NPT (27NGTF2038NPT)
1/2" x 1/2" NPT (27NGTF2012NPT)
Fusion Female Side Fusion Reduced Tee-Long Spigot §
27NTR119040F90 3" x 1 1/4" x 3"
27NTR119050F90 3" x 1 1/2" x 3"
27NTR119063F90 3" x 2" x 3"
27NTR1111040F110 3 1/2" x 1 1/4" x 3 1/2"
27NTR1111050F110 3 1/2" x 1 1/2" x 3 1/2"
27NTR1111063F110 3 1/2" x 2" x 3 1/2"
27NTR1112540F125 4" x 1 1/4" x 4"
27NTR1112550F125 4" x 1 1/2" x 4"
27NTR1112563F125 4" x 2" x 4"
27NTR1112575F125 4" x 2 1/2" x 4"
27NTR1112590F125 4" x 3" x 4"

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



27NG9011355MM 14" 27NG9011400MM 16" 27NG9011450MM 18"
27NG9011500MM 20"
Segmented 90° Elbow - Long Spigot [§] SDR 17
27NG9017355MM 14" 27NG9017400MM 16" 27NG9017450MM 18"
27NG9017500MM 20" 27NG9017560MM 22" 27NG9017630MM 24"
Segmented Tee - Long Spigot [§] SDR 11
27NT11315MM 12" 27NT11355MM 14" 27NT11400MM 16" 27NT11450MM 18" 27NT11500MM 20"
Segmented Tee - Long Spigot [§] SDR 17
27NT17315MM 12" 27NT17355MM 14" 27NT17400MM 16" 27NT17450MM 18" 27NT17500MM 20"
27NT17560MM 22" 27NT17630MM 24"
Socket Female Threaded 90° Elbow ~ [§]
1/2" x 1/2" NPT (27NGF2012NPT)
3/4" x 1/2" NPT (27NGF2512NPT)
3/4" x 3/4" NPT (27NGF2534NPT)
1" x 1/2" NPT (27NGF3212NPT)
1" x 3/4" NPT (27NGF3234NPT)
1" x 1" NPT (27NGF321NPT)
1-1/4" x 1" NPT (27NGF401NPT)
1-1/2" x 1-1/4" NPT (27NGF50114NPT)
1-1/2" x 1-1/2" NPT (27NGF50112NPT)
2" x 1" NPT (27NGF63112NPT)
2" x 2" NPT (27NGF632NPT)
Socket Female Threaded Back Plate 90° ~ [§]
1/2" x 1/2" NPT (27NTER2012NPT)
Socket Fusion 45° Elbow [§]
27NC4520 1/2" 27NC4525 3/4" 27NC4532 1"
27NC4540 1 1/4" 27NC4550 1 1/2" 27NC4563 2"
27NC4575 2 1/2" 27NC4590 3" 27NC45110 3 1/2"
27NC45125 4"
Socket Fusion 90° Elbow
N/A27NG20 1/2" 27NG25 3/4" 27NG32 1" 27NG40 1 1/4" 27NG50 1 1/2"
27NG63 2" 27NG75 2 1/2" 27NG90 3" 27NG110 3 1/2" 27NG125 4"
Socket Fusion Coupling [§]
27NMAN20 1/2" 27NMAN25 3/4" 27NMAN32 1"
27NMAN40 1 1/4" 27NMAN50 1 1/2" 27NMAN63 2"
27NMAN75 2 1/2" 27NMAN90 3" 27NMAN110 3 1/2"
27NMAN125 4"
Socket Fusion End Cap
27NCC20 1/2" 27NCC25 3/4" 27NCC32 1" 27NCC40 1 1/4" 27NCC50 1 1/2"
27NCC63 2" 27NCC75 2 1/2" 27NCC90 3" 27NCC110 3 1/2" 27NCC125 4"
Socket Fusion Male Threaded Winged 90° ~ [§]
1/2" x 3/8" NPT (27NGTM2038NPT)
1/2" x 1/2" NPT (27NGTM2012NPT)
Socket Fusion Reduced Bushing [§]
27NR2520 3/4" x 1/2" 27NR3220 1" x 1/2"
27NR3225 1" x 3/4" 27NR4020 1 1/4" x 1/2"
27NR4025 1 1/4" x 3/4" 27NR4032 1 1/4" x 1"
27NR5020 1 1/2" x 1/2" 27NR5025 1 1/2" x 3/4"
27NR5032 1 1/2" x 1" 27NR5040 1 1/2" x 1"

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



27NR6325 2" x 3/4"
27NR6340 2" x 1 1/4"
27NR7520 2 1/2" x 1/2"
27NR7532 2 1/2" x 1"
27NR7550 2 1/2" x 1 1/2"
27NR9063 3" x 2"
27NR11063 3 1/2" x 2"
27NR11090 3 1/2" x 3"
27NR125110 4" x 3 1/2"
27NR160125 6" x 4"

27NR6332 2" x 1"
27NR6350 2" x 1 1/2"
27NR7525 2 1/2" x 3/4"
27NR7540 2 1/2" x 1 1/4"
27NR7563 2 1/2" x 2"
27NR9075 3" x 2 1/2"
27NR11075 3 1/2" x 2 1/2"
27NR12590 4" x 3"
27NR160110 6" x 3 1/2"

Socket Fusion Reduced Cross [§]

27NCR402020 1 1/4" x 1/2"x 1/2" x 1 1/4"
27NCR402525 1 1/4" x 3/4" x 3/4"x 1 1/4"

Socket Fusion Reduced Tee [§]

27NTR252020 3/4" x 1/2" x 1/2"
27NTR252025 3/4" x 1/2" x 3/4"
27NTR252520 3/4" x 3/4" x 1/2"
27NTR253225 3/4" x 1" x 3/4"
27NTR323225 1" x 1" x 3/4"
27NTR322020 1" x 1/2" x 1/2"
27NTR322025 1" x 1/2" x 3/4"
27NTR322525 1" x 3/4" x 3/4"
27NTR322032 1" x 1/2" x 1"
27NTR322532 1" x 3/4" x 1"
27NTR402040 1 1/4" x 1/2" x 1 1/4"
27NTR402540 1 1/4" x 3/4" x 1 1/4"
27NTR403240 1 1/4" x 1" x 1 1/4"
27NTR502050 1 1/2" x 1/2" x 1 1/2"
27NTR502550 1 1/2" x 3/4" x 1 1/2"
27NTR503250 1 1/2" x 1" x 1 1/2"
27NTR504050 1 1/2" x 1 1/4" x 1 1/2"
27NTR632563 2" x 3/4" x 2"
27NTR633263 2" x 1" x 2"
27NTR634063 2" x 1 1/4" x 2"
27NTR635063 2" x 1 1/2" x 2"
27NTR753275 2 1/2" x 1" x 2 1/2"
27NTR754075 2 1/2" x 1 1/4" x 2 1/2"
27NTR755075 2 1/2" x 1 1/2" x 2 1/2"
27NTR756375 2 1/2" x 2" x 2 1/2"
27NTR906390 3" x 2" x 3"
27NTR907590 3" x 2 1/2" x 3"
27NTR11063110 3 1/2" x 2" x 3 1/2"
27NTR11075110 3 1/2" x 2 1/2" x 3 1/2"
27NTR11090110 3 1/2" x 3" x 3 1/2"
27NTR12575125 4" x 2 1/2" x 4"
27NTR12590125 4" x 3" x 4"
27NTR125110125 4" x 3 1/2" x 4"

Socket Fusion Side Elbow Three Outlets [§]

27NCTV20 1/2"
Socket Fusion Street 45° Elbow [§]

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



27NCMF4520 1/2" 27NCMF4525 3/4"
Socket Fusion Street 90° Elbow §

27NGMF20 1/2" 27NGMF25 3/4" 27NGMF32 1" 27NGMF40 1 1/4"
Socket Fusion Tee

27NT20 1/2" 27NT25 3/4" 27NT32 1" 27NT40 1 1/4" 27NT50 1 1/2"
27NT63 2" 27NT75 2 1/2" 27NT90 3" 27NT110 3 1/2" 27NT125 4"
Socket Long Radius 90° Elbow §

27NCLR20 1/2" 27NCLR25 3/4"
Socket Male Threaded 90° Elbow ~ §

1/2" x 1/2" NPT (27NGM2012NPT) 3/4" x 1/2" NPT (27NGM2512NPT)
3/4" x 3/4" NPT (27NGM2534NPT) 1" x 1/2" NPT (27NGM3212NPT)
1" x 3/4" NPT (27NGM3234NPT) 1" x 1" NPT (27NGM321NPT)
Street 45° Elbow - Socket Fusion §

27NC45MF20 1/2" 27NC45MF25 3/4" 27NC45MF32 1"
Stub Flange - Long Spigot §

27NCRT3211 1" 27NCRT4011 1 1/4" 27NCRT5011 1 1/2"
27NCRT6311 2" 27NCRT7511 2 1/2" 27NCRT9011 3"
27NCRT11011 3 1/2" 27NCRT12511 4" 27NCRT16011 6"
27NCRT20011 8" 27NCRT25011 10"
Stub Flange - Short Spigot § SDR 11

27NCRT31511S 12" 27NCRT35511S 14" 27NCART40011S 16"
27NCRT45011S 18" 27NCRT50011S 20"
Tee - Long Spigot § SDR 7.3

27NT7363MM 2" 27NT7375MM 2 1/2" 27NT7390MM 3"
27NT73110MM 3 1/2" 27NT73125MM 4" 27NT73160MM 6"
Tee - Long Spigot § SDR 11

27NT11315MMA 12" Tee - Long Spigot § SDR 17

27NT17315MMA 12" Tee - Long Spigot (Injected Alongated) § SDR 11

27NT11355MMC 14" 27NT11400MMC 16" 27NT11450MMC 18"
Tee - Long Spigot (Injected Alongated) § SDR 17

27NT17355MMC 14" 27NT17400MMC 16" 27NT17450MMC 18"
Tee - Long Spigot (Segmented Fitting) § SDR 11

27NT11315MMB 12" 27NT11355MMB 14" 27NT11400MMB 16"
27NT11450MMB 18" 27NT11500MMB 20"
Tee - Long Spigot (Segmented Fitting) § SDR 17

27NT17315MMB 12" 27NT17355MMB 14" 27NT17400MMB 16"
27NT17450MMB 18" 27NT17500MMB 20" 27NT17560MMB 22"
27NT17630MMB
Tee - Plain Long Spigot (Segmented Fitting) § SDR 7.3

27NT73200MMB 8" 27NT73250MMB 10" 27NT73315MMB 12"
27NT73355MMB 14"
Template for External Bath Taps §

27NGVF2012NPT 1/2" x 1/2" 27NGVF2512NPT 3/4" x 1/2"
Welding Saddles Socket Fusion Outlet

1/2" x 1 1/2" (27NGS2050)
3/4" x 1 1/2" (27NGS2550)

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



- 1/2"x 2"/2 1/2" (27NGS206375)
- 3/4"x 2"/2 1/2" (27NGS256375)
- 1"x 2"/2 1/2" (27NGS326375)
- 1/2"x 2"/2 1/2" (27NGS206375)
- 3/4"x 2"/2 1/2" (27NGS256375)
- 1/2"x3"/3 1/2"/4" (27NGS2090110125)
- 3" x 3/4" (27NGS9025)
- 1"x 3"/3 1/2"/4" (27NGS3290110125)
- 3/4"x 3"/3 1/2"/4" (27NGS2590110125)
- 2" x 4" (27NGS63125)
- 1 1/4"x 6"/8" (27NGS40160200)
- 2" x 6" (27NGS63160)

! Products which are Certified to the Uniform Plumbing Code™ are exempt from the requirement to mark the fitting with the U.P. Code Mark.

~ With NPT Lead Free Brass

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.

+++ Material complies with NSF/ANSI/CAN 61 health effects requirements when tested at temperatures up to and including Commercial Hot (180° F).

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility: Castel Guelfo di Bologna (BO), Italy

Potable Water - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe & § +++ [G]	PP-RCT	Niron Grey	ASTM F2389
27TNIRR2073 - 20 mm (½")	SDR 7.3		
27TNIRR2573 - 25 mm (¾")	SDR 7.3		
27TNIRR329 - 32 mm (1")	SDR 9		
27TNIRR4011 - 40 mm (1 ¼")	SDR 11		
27TNIRR5011 - 50 mm (1 ½")	SDR 11		
27TNIRR6311 - 63 mm (2")	SDR 11		
27TNIRR7511 - 75 mm (2 ½")	SDR 11		
27TNIRR9011 - 90mm (3")	SDR 11		
27TNIRR11011 - 110 mm (3 ½")	SDR 11		
27TNIRR12511 - 125 mm (4")	SDR 11		
27TNIRR16011 - 160 mm (6")	SDR 11		
27TNIRR6317 - 63 mm (2")	SDR 17		
27TNIRR7517 - 75 mm (2 ½")	SDR 17		
27TNIRR9017 - 90 mm (3")	SDR 17		
27TNIRR11017 - 110 mm (3 1/2")	SDR 17		
27TNIRR12517 - 125 mm (4")	SDR 17		
27TNIRR16017 - 160 mm (6")	SDR 17		
Pipe & § +++ [G]	PP-RCT	Niron Blue	ASTM F2389
27TNIRRB2073 - 20 mm (½")	SDR 7.3		
27TNIRRB2573 - 25 mm (¾")	SDR 7.3		
27TNIRRB329 - 32 mm (1")	SDR 9		

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



27TNIRRB4011 - 40 mm (1 ¼")	SDR 11
27TNIRRB5011 - 50 mm (1 ½")	SDR 11
27TNIRRB6311 - 63 mm (2")	SDR 11
27TNIRRB7511 - 75 mm (2 ½")	SDR 11
27TNIRRB9011 - 90mm (3")	SDR 11
27TNIRRB11011 - 110 mm (3 ½")	SDR 11
27TNIRRB12511 - 125mm (4")	SDR 11
27TNIRRB16011 - 160 mm (6")	SDR 11
27TNIRRB6317 - 63 mm (2")	SDR 17
27TNIRRB7517 - 75 mm (2 ½")	SDR 17
27TNIRRB9017 - 90 mm (3")	SDR 17
27TNIRRB11017 - 110 mm (3 ½")	SDR 17
27TNIRRB12517 - 125 mm (4")	SDR 17
27TNIRRB16017 - 160 mm (6")	SDR 17
<i>Pipe & S + + + [G]</i>	
27TNIRCL2073 - 20 mm (¾")	SDR 7.3
27TNIRCL2573 - 25 mm (¾")	SDR 7.3
27TNIRCL3273 - 32 mm (1")	SDR 7.3
27TNIRCL4073 - 40 mm (1 ¼")	SDR 7.3
27TNIRCL5073 - 50 mm (1 ½")	SDR 7.3
27TNIRCL6373 - 63 mm (2")	SDR 7.3
27TNIRCL7573 - 75 mm (2 ½")	SDR 7.3
27TNIRCL9073 - 90 mm (3")	SDR 7.3
27TNIRCL11073 - 110 mm (3 ½")	SDR 7.3
27TNIRCL12573 - 125 mm (4")	SDR 7.3
27TNIRCL16073 - 160 mm (6")	SDR 7.3
27TNIRCL20073 - 200 mm (8")	SDR 7.3
27TNIRCL25073 - 250 mm (10")	SDR 7.3
27TNIRCL31573 - 315 mm (12")	SDR 7.3
27TNIRCL329 - 32 mm (1")	SDR 9
27TNIRCL409 - 40 mm (1 ¼")	SDR 9
27TNIRCL509 - 50 mm (1 ½")	SDR 9
27TNIRCL639 - 63 mm (2")	SDR 9
27TNIRCL759 - 75 mm (2 ½")	SDR 9
27TNIRCL909 - 90 mm (3")	SDR 9
27TNIRCL1109 - 110 mm (3 ½")	SDR 9
27TNIRCL1259 - 125 mm (4")	SDR 9
27TNIRCL1609 - 160 mm (6")	SDR 9
27TNIRCL2009 - 200 mm (8")	SDR 9
27TNIRCL2509 - 250 mm (10")	SDR 9
27TNIRCL3159 - 315 mm (12")	SDR 9
27TNIRCL3559 - 355 mm (14")	SDR 9
27TNIRCL2511 - 25 mm (¾")	SDR 11
27TNIRCL3211 - 32 mm (1")	SDR 11
27TNIRCL4011 - 40 mm (1 ¼")	SDR 11
27TNIRCL5011 - 50 mm (1 ½")	SDR 11
27TNIRCL6311 - 63 mm (2")	SDR 11

PP-RCT

Niron Clima

ASTM F2389

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



27TNIRCL7511 - 75 mm (2 ½")	SDR 11
27TNIRCL9011 - 90 mm (3")	SDR 11
27TNIRCL11011 - 110 mm (3 ½")	SDR 11
27TNIRCL12511 - 125 mm (4")	SDR 11
27TNIRCL16011 - 160 mm (6")	SDR 11
27TNIRCL20011 - 200 mm (8")	SDR 11
27TNIRCL25011 - 250 mm (10")	SDR 11
27TNIRCL31511 - 315 mm (12")	SDR 11
27TNIRCL35511 - 355 mm (14")	SDR 11
27TNIRCL40011 - 400 mm (16")	SDR 11
27TNIRCL45011 - 450 mm (18")	SDR 11
27TNIRCL50011 - 500 mm (20")	SDR 11
27TNIRCL6317 - 63 mm (2")	SDR 17
27TNIRCL7517 - 75 mm (2 ½")	SDR 17
27TNIRCL9017 - 90 mm (3")	SDR 17
27TNIRCL11017 - 110 mm (3 ½")	SDR 17
27TNIRCL12517 - 125 mm (4")	SDR 17
27TNIRCL16017 - 160 mm (6")	SDR 17
27TNIRCL20017 - 200 mm (8")	SDR 17
27TNIRCL25017 - 250 mm (10")	SDR 17
27TNIRCL31517 - 315 mm (12")	SDR 17
27TNIRCL35517 - 355 mm (14")	SDR 17
27TNIRCL40017 - 400 mm (16")	SDR 17
27TNIRCL45017 - 450 mm (18")	SDR 17
27TNIRCL50017 - 500 mm (20")	SDR 17
27TNIRCL56017 - 560 mm (22")	SDR 17
27TNIRCL63017 - 630 mm (24")	SDR 17

Pipe & S + + + [G]

PP-RCT

Niron FG

ASTM F2389

27TNIRRF2073 - 20 mm (½")	SDR 7.3
27TNIRRF2573 - 25 mm (¾")	SDR 7.3
27TNIRRF3273 - 32 mm (1")	SDR 7.3
27TNIRRF4073 - 40 mm (1 ¼")	SDR 7.3
27TNIRRF5073 - 50 mm (1 ½")	SDR 7.3
27TNIRRF6373 - 63 mm (2")	SDR 7.3
27TNIRRF7573 - 75 mm (2 ½")	SDR 7.3
27TNIRRF9073 - 90 mm (3")	SDR 7.3
27TNIRRF11073 - 110 mm (3 ½")	SDR 7.3
27TNIRRF12573 - 125 mm (5")	SDR 7.3
27TNIRRF16073 - 160 mm (6")	SDR 7.3
27TNIRRF329 - 32 mm (1")	SDR 9
27TNIRRF409 - 40 mm (1 ¼")	SDR 9
27TNIRRF509 - 50 mm (1 ½")	SDR 9
27TNIRRF639 - 63 mm (2")	SDR 9
27TNIRRF759 - 75 mm (2 ½")	SDR 9
27TNIRRF909 - 90 mm (3")	SDR 9
27TNIRRF1109 - 110 mm (3 ½")	SDR 9
27TNIRRF1259 - 125 mm (4")	SDR 9

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



27TNIRRF1609 - 160 mm (6")	SDR 9
27TNIRRF4011 - 40 mm (1 1/4")	SDR 11
27TNIRRF5011 - 50 mm (1 1/2")	SDR 11
27TNIRRF6311 - 63 mm (2")	SDR 11
27TNIRRF7511 - 75 mm (2 1/2")	SDR 11
27TNIRRF9011 - 90 mm (3")	SDR 11
27TNIRRF11011 - 110 mm (3 1/2")	SDR 11
27TNIRRF12511 - 125 mm (4")	SDR 11
27TNIRRF16011 - 160 mm (6")	SDR 11

& Pipe also meets the chlorine resistance requirement of CL-TD in accordance with ASTM F2023.

* This product is certified for grey color pipe and grey color pipe with a non-wetted red stripe on the outside of the pipe only.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.

+++ Material complies with NSF/ANSI/CAN 61 health effects requirements when tested at temperatures up to and including Commercial Hot (180° F).

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.